

Canadian Association of Physicists - Congress

Quebec – June 2-5 2002


Overview of ATLAS Canada Calorimeter Projects



Robert S. Orr

University of Toronto
on behalf of the
ATLAS Canada Group

Progress of the ATLAS Canada Detector Projects



CANADA

Liquid Argon Calorimeters

Electronics

Computing & Event Filters


Physics Studies

Construction Status of the Detector Components

- High Centre of Mass Energy - 14 TeV
- High Luminosity - $10^{34} \text{ cm}^{-2} \text{ s}^{-1}$


D712imb-26/06/97

Magnet system
Inner detector
Calorimetry
Muon instrumentation
TDAQ and computing
Infrastructure and
experimental area




Experimental Area

Most of the surface building will be handed over to ATLAS this year (Oct-Nov 2002)



Underground civil engineering will end in Spring 2003

ATLAS will start installation at Point-1 in April 2003




Excavation will end in May 2002



Point 1 - UX15 bench excavation - April 08, 2002 - CERN ST-CE

Status of ATLAS Overall

- **LHCC Milestones = Progress Monitor.**
- **Passed milestones compared to the planning.**
- **Adjusted spring 2001, after the LHC project schedule change at that time.**
- **BEAM IN SPRING 2007**




Status of ATLAS Overall

Financial Situation - Initial Staged Detector


- **Discovery Potential for Higgs Degraded by 10%**
- **Need 20% more Lumi to Compensate**

| Staged items | Main impact expected on | Loss in significance |
|----------------------------|-------------------------|-------------------------------|
| One pixel layer | $ttH \rightarrow ttbb$ | ~ 8% |
| Outermost TRT wheels + MDT | $H \rightarrow 4\mu$ | ~ 7% |
| Cryostat Gap scintillators | $H \rightarrow 4e$ | ~ 8% |
| MDT | $A/H \rightarrow 2\mu$ | ~ 10% for $m \sim 300$ GeV |

Higgs production via Vector Boson Fusion



$\sigma \approx 4$ pb is $\sim 20\%$ of the total Higgs cross-section for $m_H \sim 120$ GeV
 However: distinctive signature of two very forward jets + little additional jet activity (tools against background)




$qqH \rightarrow qqWW \rightarrow qq \mu\nu e\nu$


$S/\sqrt{B} \sim 8$ for 10 fb^{-1}
 $m_H = 160$ GeV

$qqH \rightarrow qq \tau\tau \rightarrow qq\mu e + X$


$S/\sqrt{B} \sim 3$ for 30 fb^{-1}
 $m_H = 120$ GeV
 (10% B systematics included)



Higgs discovery potential for 30 fb^{-1} in the low-mass region



Higgs discovery potential for 10 fb^{-1} in the low-mass region



Vector boson fusion channels (in particular WW^*) are discovery channels at low luminosity

For 10 fb^{-1} ATLAS alone:

$\geq 5 \sigma$ significance for
 $120 \leq m_H \leq 190 \text{ GeV}$

by combining standard $H \rightarrow \gamma\gamma$ and $ttH \rightarrow ttbb$ channels with VBF channels

VBF channels improve the sensitivity significantly in the low mass region

Several channels available over the full mass range (important for Higgs parameter determination)

LAr Calorimetry

- General Requirements

Fast readout scheme
Radiation hard
High segmentation
Uniformity of response
Dynamic range (from 1 mip to 5 TeV)
Hermiticity down to $|\eta| \approx 5$
Long term stability
“Ease” of calibration

- Physics Requirements

Discovery Physics - Higgs, SUSY,
Precision Physics - t, b, ...


Reconstruction $P_e, P_\gamma, P_{\text{jet}}, E_T^{\text{miss}}, (P_\mu), \text{bunch}$
Separation $\gamma/\pi^0, e/\pi$

- Mechanical consideration:

cost
modular construction
installation in ATLAS

LAr Calorimetry

- Five different detectors, different technologies
- Needed for ATLAS calorimetry coverage to $|\eta| \cong 5$



LAr Calorimeter Technology Overview

Design Goals  Technology

- **EM Calorimeters** ($0 \leq |\eta| \leq 3.2$) and **Presampler** ($0 \leq |\eta| \leq 1.8$)


$$\frac{\sigma}{E} \leq \frac{10\%}{\sqrt{E(\text{GeV})}} \oplus 0.7\% \oplus \frac{0.27}{E(\text{GeV})} \quad \sigma_{\theta} \leq \frac{40 \text{ mrad}}{\sqrt{E(\text{GeV})}} \quad \sigma_{\bar{r}} \leq \frac{8 \text{ mm}}{\sqrt{E(\text{GeV})}}$$

 Lead/Copper-Kapton/Liquid Argon *Accordion* Structure


- **Hadronic Endcap** ($1.5 \leq |\eta| \leq 3.2$) $\frac{50\%}{\sqrt{E(\text{GeV})}} \oplus 3\% \leq \frac{\sigma}{E}(\text{jets}) \leq \frac{100\%}{\sqrt{E(\text{GeV})}} \oplus 10\%$


 Copper/Copper-Kapton/Liquid Argon *Plate* Structure

- **Forward Calorimeter** ($3 \leq |\eta| \leq 5$) $\frac{\sigma}{E}(\text{jets}) \leq \frac{100\%}{\sqrt{E(\text{GeV})}} \oplus 10\%$


 Tungsten/Copper/Liquid Argon *Paraxial Rod* Structure

ATLAS Calorimetry





LAr Barrel Cryostat and Feedthroughs



- **Barrel Cryostat is at CERN ready detector installation:**

- Integration work is now finished

- All feedthroughs installed (signal and HV)

- All cryolines installed

- Leak tests successfully done

- **Next steps:**


- EM calorimeter installation

- Nov 2002 to June 2003

- Install solenoid

- July 2003

LAr End-Cap Cryostats and Feedthroughs



Cryostat
Cold Vessel

Interaction
Point
End


FCAL

Cryostat Warm
Vessel



HEC Assembly



Rotator




Wheel

T6 Cryostat

Liquid Argon Signal Feedthroughs



EndCap
Cryostat



8-row pin carrier




Warm/cold flange

Over 180k signal channels in the LAr calorimetry
High density and reliability required:
1920 pins per feedthrough unit
barrel: 64 units
endcaps: 50 units total

Electromagnetic Barrel


$$0 < \eta < 1.4$$



Barrel Module Schematic
with presampler

- 64 gaps /module
- 2.1 mm gap
- 2x3100 mm long


Half Barrel Assembly




- 2x16 modules
- I.R/O.R 1470/2000 mm
- 22 - 33 X_0
- 3 longitudinal samples
- $\Delta\eta \times \Delta\varphi$ 0.025 x 0.025
- presampler $|\eta| < 1.8$

Electromagnetic Endcap

$$1.4 < \eta < 3.2$$



- 96 gaps /module outer wheel
32 gaps/module inner wheel
- 2.8 - 0.9 mm gap outer
3.1-1.8 mm inner




- 2x8 modules
- Diam. 4000 mm
- 22 - 37 X_0
- 3 longitudinal samples
- Front sampling of 6 X_0
for $|\eta| < 2.5$, η - strips.
- $\Delta\eta \times \Delta\varphi$ 0.025 \times 0.025
 $|\eta| > 2.5 \rightarrow 0.1 \times 0.1$

Accordion Structure





Pb Absorber

Barrel absorbers




- Honeycomb spacer
- &
- Cu/Kapton electrode



EM Barrel Module



Trial assembly of two EM barrel modules




Presampler




Electromagnetic Endcap


Back



Front




Detail of Kaptons




Electromagnetic Endcap

Test Beam Spatial Resolution



Resolution satisfactory
< 0.3 mm in strip section

Test Beam Angular Resolution




Resolution satisfactory
< 50 mrad/ \sqrt{E} on angular measurements

Electromagnetic Cal. Test Beam Energy Resolution


Barrel

Energy resolution




Endcap


Energy resolution at $\eta = 1.9$



Test Beam Presampler




$E_{\text{Presampler}}$



$E_{\text{Presampler}}$


E_{BEAM}

Energy Resolution





Presampler Weight

E corrected by presampler



Hadronic Endcap Calorimeter

LAr-Cu sampling calorimeter covering $1.5 < \eta < 3.2$



Composed of 2 wheels per end, 32 modules per wheel


Front wheel: 67 t25 mm Cu plates

Back wheel: 90 t50 mm Cu plates




HEC Module Structure

HEC Read-out Scheme

- The read-out structure is **electrostatic transformer**:
 - Small gap avoids ion build-up
 - Same behaviour as a 4 mm gap with lower HV (2 kV instead of 4 kV)
- Reduce capacitance seen by the preamplifiers, only 2 gaps are read (4 mm out of 8 mm of LAr)
- The GaAs preamplifiers in LAr.
- Cells are fully pointing in azimuth, but only « pseudo-pointing » in η
- Robust against H.V. shorts




HEC Module Assembly for Testbeam



HEC Test Beam


Electron Energy Resolution

$$\frac{\sigma(E)}{E} = \frac{21.4 \pm 0.2\%}{\sqrt{E_0(\text{GeV})}} \oplus 0.3 \pm 0.2\%$$




Pion Energy Resolution

$$\frac{\sigma(E)}{E} = \frac{(70.6 \pm 1.5)\%}{\sqrt{E_0(\text{GeV})}} \oplus (5.8 \pm 0.2)\%$$




HEC Testbeam

Muon Detection





150 GeV muons

Signal Model



HEC Test Beam

Spatial uniformity of response to electrons as a variation of EM calib. Const. variation




Non-uniformity < 1%

Forward Calorimeter

Modules


0.9 m Diameter

.45 m long



| | FCAL1 | FCAL2 | FCAL3 |
|---------------------|-------|-------|-------|
| η_{\min} | 3.0 | 3.1 | 3.2 |
| η_{\max} | 4.9 | 4.9 | 4.9 |
| Absorber material | Cu | W | W |
| Mass (t) | 2.3 | 4.1 | 4.0 |
| dE/dx sampling % | 1.49 | 1.36 | 1.68 |
| Depth (λ) | 2.6 | 3.5 | 3.4 |
| Gap width (mm) | 0.25 | 0.375 | 0.50 |
| Drift time (ns) | 50 | 75 | 100 |


FCAL Electrode Structure




FCAL1

FCAL2/3

FCAL3 TUBE-ROD UNIT




Copper Module Concept




Tungsten Module Concept

FCAL3 MATRIX




FCAL1 Module

Inserting electrode tube




Stack of Cu Plates




FCAL2/3 Assembly

March 2001




September 2001

Tungsten Module Assembly




Laying W slugs

Adjustment of slug gap




FCAL2/3 Assembly


Liquid Argon Gap



Tungsten Rod




Energy Resolution



1998 Test Beam

FCAL Hadronic Linearity

$\frac{1}{4}(FCAL1+FCAL2)$



Conclusion

- ATLAS on Track for Data in 2007
- Canadian Construction Projects Well Advanced
- Just have to wait for Eagerly Anticipated Physics

